

# VX-230 Series

## VHF/UHF Portable Radios

### SPECIFICATION SHEET

### Compact Radio with Long-Lasting Li-Ion Battery

The Vertex Standard VX-231 provides wide band coverage, more signaling features and improved ergonomics\* that adds up to a better return on your investment.

#### Improved Portability

A radio that won't get in the way, the VX-231 is more compact and lightweight than the VX-160 series. A radio that is easier to carry with you on the job.

#### More Battery Power

Designed to use powerful Li-Ion battery technology for longer battery life. Includes a 1150 mAh battery providing 9 hours of operation with the battery saver enabled.

Or choose the optional 2000 mAh Li-Ion battery for up to 16.5 hours battery life.

#### Wide Band Coverage for Added Value

One radio designed to cover the full band in the VHF and upper range of the UHF bands, which provides expanded options in frequencies to use.

#### More Scanning Options

While many radios provide 1 or 2 scanning options, the VX-231 radio gives you 4 additional scanning options for greater convenience and flexibility for the way you need your radios to perform. Options include: Priority, Dual Watch, Follow Me and Talk Around scan.

#### Exclusive Auto-Range Transponding System – ARTS™

Only Vertex Standard radios are designed to inform you when you and another ARTS™-equipped station are within communication range. If out of range for more than 2 minutes, your radio senses no signal has been received and beeps to alert you. The base station can then alert the field unit to move back in range. A great solution to keep your workers coordinated.

\*Compared to VX-160 series.



#### The Vertex Standard Difference

Our number one goal is achieving superior customer satisfaction by delivering products and services that exceed your expectations. Vertex Standard radios are built to last and are backed by an industry-leading 3 year warranty – another great reason to choose Vertex Standard. Ask your Dealer for more details.



4.3" (H) X 2.3" (W) X 1.2" (D)



### Additional Features

- 16 channel capacity
- Two programmable keys
- Flexible channel spacing: 12.5 kHz to 25 kHz
- Battery power save option
- Emergency
- Lone Worker
- DTMF ANI
- DTMF Speed Dial
- 2-Tone Encode and Decode
- CTCSS / DCS Encode and Decode
- Manual squelch adjustment
- Radio-to-radio cloning

### Accessories

- MH-450S: Speaker microphone
- MH-360S: Compact speaker microphone
- MH-45B4B: Noise cancelling speaker microphone
- MH-37A4B: Earpiece microphone
- VH-115S: Behind-the-head headset w/boom mic
- VH-215S: Over-the-head single-muff headset
- VC-25: Over-the-head VOX headset
- FNB-V104LI: 2000 mAh Li-Ion battery
- FNB-V103LI: 1150 mAh Li-Ion battery
- VAC-300: Desktop rapid charger (Li-Ion only)
- DCM-1: Desktop charger mounting adapter
- VCM-2: Vehicle charger mounting adapter
- VAC-6300: 6-Unit multi rapid charger (Li-Ion only)
- LCC-350: Leather case
- LCC-350S: Leather case w/swivel belt clip
- CLIP-18: Belt clip
- CLIP-17E: Swivel belt clip

### VX-230 Series Specifications

	VHF	UHF
<b>General Specification</b>		
Frequency Range	134 MHz - 174 MHz	400 - 470 MHz; 450 - 512MHz
Number of Channels	16	
Power Supply Voltage	7.4V DC±20%	
Channel Spacing	12.5/20/25 kHz	
PLL Steps	2.5/5/6.25 kHz	5/6.25 kHz
Battery Life (5-5-90 duty)	9.0 hours (7.3 hours w/o saver)	
1150 mAh FNB-V103LI	16.5 hours (13.5 hrs w/o saver)	
2000 mAh FNB-V104LI		
IP Rating	IP54	
Operating Temperature Range	-22° F to +140° F (-30° C to +60° C)	
Frequency Stability	±2.5 ppm	
RF Input-Output Impedance	50 Ohms	
Dimension (H x W x D)	4.3 x 2.3 x 1.2 inches (110 x 58 x 30 mm) (w/ FNB-V103LI)	
Weight (Approx.)	10.1 oz. (285g) (w/FNB-V103LI, Antenna, Belt Clip)	
<b>Receiver Specification: measured by TIA/EIA-603</b>		
Sensitivity 12dB SINAD	0.25. µV typical	
Adjacent Channel Selectivity	65 / 60 dB 25 kHz / 12.5 kHz	
Intermodulation	65 / 60 dB 25 kHz / 12.5 kHz	
Spurious and Image Rejection	65 dB	
Audio Output	500mW @ 4 Ohms 5% THD	
<b>Transmitter Specification: measured by TIA/EIA-603</b>		
Output Power	5 / 1 W	
Modulation	16K0F3E, 11K0F3E	
Conducted Spurious Emissions	65 dB below carrier	
FM Hum & Noise	45 / 40 dB 25 kHz / 12.5 kHz	
Audio Distortion	< 3 % @1kHz	

### Applicable MIL-STD

Standard	MIL 810C Methods/ Procedures	MIL 810D Methods/ Procedures	MIL 810E Methods/ Procedures	MIL 810F Methods/ Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I Cat.A1	505.2/Procedure I Cat.A1	505.4/Procedure I Cat.A1
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4/Procedure I
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4/Procedure I
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure X	514.3/Procedure I Cat. 10	514.4/Procedure I Cat. 10	514.4/Procedure I Cat. 24
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, V

Specifications are subject to change without notice or obligation.

VERTEX STANDARD is registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. © Vertex Standard Co. Ltd. 2009

NSS230\_11/2009\_S